



Anybus X-gateway – CC-Link Slave - CC-Link Slave

The Anybus X-gateway allows you to seamlessly inter-connect/extend PLC control systems and their connected devices on a CC-Link network.

FAST COPYING OF I/O DATA

The X-gateways primary function is with the fast transfer of cyclic I/O data between the two PLC systems. This offloads your PLC from working with additional calculations. The gateway acts as a Slave and provides a simple network extension. The data transmission is completely transparent with a maximum data capacity of 512 bytes in each direction.

EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

The connection between the two networks is quickly set up in the Anybus Configuration Manager software, included with the X-gateway. No programming skills are needed to set up the X-gateway. As factory default the X-gateways have a pre-defined I/O size of 20 bytes I/O.



CC-Link

Features and benefits

- Fast copying of cyclic I/O data between the two CC-Link networks (10-15 ms)
- Proven and tested with all PLC manufacturers
- Supports up to a maximum of 512 bytes of Input and Output data in each direction
- Optional control and status information added to the I/O data for diagnostic purposes
- Robust stand-alone housing for use in harsh industrial environments
- Global free technical support and consultancy

CC-Link Slave interface

CC-Link Slave settings can be made either via on-board switches, or by importing the provided .CSP file into engineering tool of the controlling PLC.

- Complete CC-Link slave Version 1 and 2 functionality
- CC-Link Conformance BAP-05027-B specification
- Transparent CC-Link communication (Standard Mode)
- PLC Profile compliant communication (PLC profile mode)
- Max. 896 bits/128 words (368 bytes) of I/O data in each direction
- Supports CC-Link baudrates 156 kbit/s – 10 Mbit/s
- Up to 4 occupied stations
- Up to 8 extension cycles (version 2 only)
- CC-Link configuration via on-board switches or via .CSP file
- x 5-pin, 5.08 Phoenix plug network connector

CC-Link Slave interface

CC-Link Slave settings can be made either via on-board switches, or by importing the provided .CSP file into engineering tool of the controlling PLC.

- Complete CC-Link slave Version 1 and 2 functionality
- CC-Link Conformance BAP-05027-B specification
- Transparent CC-Link communication (Standard Mode)
- PLC Profile compliant communication (PLC profile mode)
- Max. 896 bits/128 words (368 bytes) of I/O data in each direction
- Supports CC-Link baudrates 156 kbit/s – 10 Mbit/s
- Up to 4 occupied stations
- Up to 8 extension cycles (version 2 only)
- CC-Link configuration via on-board switches or via .CSP file
- 1x 5-pin, 5.08 Phoenix plug network connector

TECHNICAL SPECIFICATIONS

Dimensions (L•W•H)	114 x 44 x 127mm or 4,49 x 1,73 x 5,00"
Weight	400g or 0,880 lbs
Operating temperature	-25 to +65 °C or -13 to +149 °F
Storage temperature	-40 to +85 °C or -40 to +185 °F
Power supply	24 VDC +/- 20% via 2-pole 5.08 mm Phoenix pluggable screw connector
Current consumption	max. 400mA (Typical 200mA)
Enclosure material	Aluminium and plastic
Installation position	Vertical / Flat*
Galvanic isolation	YES, on both BUS/Ethernet side
Mechanical rating	IP20, NEMA rating 1
Mounting	DIN-rail (EN 50022 standard)
I/O configuration	via USB port with Anybus Configuration Manager software
Certifications	CE, cULUS, RoHS

File	Version	Size	Read online
------	---------	------	-------------

Ordering information

Order Code	AB7626
Included components	Gateway Quick start documentation USB configuration cable Power supply not included Configuration software is available for download.

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.