



Anybus X-gateway – Interbus FO Slave - Modbus TCP Server

The Anybus X-gateway allows you to seamlessly inter-connect PLC control systems and their connected devices between Interbus Fiber Optic and Modbus TCP networks.

FAST COPYING OF I/O DATA

The X-gateways primary function is with the fast transfer of cyclic I/O data between the two networks. This offloads your PLC from working with additional calculations. The gateway acts as an Slave/Server on both networks. The data transmission is completely transparent with a maximum data capacity of 512 bytes in each direction.

EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

The connection between the two networks is quickly set up in the Anybus Configuration Manager software, included with the X-gateway. No programming skills are needed to set up the X-gateway. As factory default the X-gateways have a pre-defined I/O size of 20 bytes I/O.



Features and benefits

- Fast copying of cyclic I/O data between the two networks (10-15 ms)
- Proven and tested with all PLC manufacturers
- Supports up to a maximum of 512 bytes of Input and Output data in each direction
- Possibility to build web pages displaying and controlling a factory floor process with data from the other connected network
- Fast, dynamic transfer of fieldbus data to e.g. SCADA/HMI/Enterprise level systems based on Microsoft Windows, via the included Anybus OPC server
- Optional control status information added to I/O data for diagnostic purposes
- Robust stand-alone housing for use in harsh industrial environments
- Global free technical support and consultancy

Interbus Fiber Optic Slave Interface

Interbus Slave address settings can be automatically detected by the controlling PLC.

- Complete Interbus functionality according to EN 50170
- Fiber Optic features FSMA standard connectors conforming to IEC874-2 and DIN47258
- Based on OPC chipset with support for optical diagnostics
- Transmission Media: Plastic fibre, core 980um, clad 1000um: HCS (glass) fibre, core 200um, clad 230 um
- Max. 20 bytes of process data (512 bytes with PCP) in each direction
- PCP V.2.0. (0, 1, 2, or 4 words)
- Interbus baudrate 500 kbit/s – 2 Mbit/s

• Automatic slave address detection by controlling PLC master

• 1x HFBR-2505C and 1x HFBR-1505C Fiber Optic network connectors

Modbus TCP Slave interface

Modbus TCP Slave settings can be made either via the built-in web interface, or by importing the provided .EDS file into engineering tool of the controlling PLC.

- Conforms to Modbus TCP v1.0
- Modbus TCP class 0, class 1 and partially class 2 slave functionality
- 10/100Mbit operation in full or half-duplex
- Integrated FTP server provides easy file management using standard FTP clients
- Web server with dynamic data capability and Server Side Include (SSI) capability
- Email client with dynamic data capability and Event-triggered email handling
- Per-user security framework
- Quality of Service (QoS) available
- DNS Capability
- TCP/IP settings via DHCP/ARP/Anybus IPconfig (HICP)
- Integrated switch allowing for a daisy-chain topology
- 2x RJ-45 ports available simultaneously.

TECHNICAL SPECIFICATIONS

Dimensions (L•W•H)	114 x 44 x 127mm or 4,49 x 1,73 x 5,00"
Weight	400g or 0,880 lbs
Operating temperature	-25 to +65 °C or -13 to +149 °F
Storage temperature	-40 to +85 °C or -40 to +185 °F
Power supply	24 VDC +/- 20% via 2-pole 5.08 mm Phoenix pluggable screw connector
Current consumption	max. 400mA (Typical 200mA)
Enclosure material	Aluminium and plastic
Installation position	Vertical / Flat*
Galvanic isolation	YES, on both BUS/Ethernet side
Mechanical rating	IP20, NEMA rating 1
Mounting	DIN-rail (EN 50022 standard)
I/O configuration	via USB port with Anybus Configuration Manager software
Certifications	CE, CULUS, RoHS

File	Version	Size	Read online
------	---------	------	-------------

Ordering information

Order Code	AB7639
Included components	Gateway Quick start documentation USB configuration cable

Power supply **not** included

Configuration and Anybus OPC server software is available for download.

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#)

Copyright © 2020 HMS Industrial Networks - All rights reserved.